



SMART
LAUNDRY
TECHNOLOGY



Commercial Heavy-duty
Frontload Dryer Electric



MODEL
ELECTRIC
FDE3TRGS301NW10
10KGS

DIMENSIONS & SPECIFICATIONS

CYLINDER VOLUME CU. FT (LITERS)	7.0 (198)	ELECTRICAL SPECIFICATIONS	ELECTRIC 123/240/60/1-30AMP 120/208/60/1-30AMP
WIDTH - IN (MM)	26 7/8* (683)		230/60/1-30 AMP
DEPTH - IN (MM)	28* (711)		400/50/3-15 AMP
HEIGHT - IN (MM)	43*(1092)		GAS: 120/60/1-15AMP
WORK SURFACE HEIGHT- IN (MM)	36* (914)		230/50/1-10AMP
WEIGHT-LB (KG)	ELECTRIC 130 (59) GAS 135 (61)	MOTOR-RPM	60 HZ: 1725
	ELECTRIC 140 (64) GAS 145(66)	BTU PER HOUR	22.500 (5670 KCAL)
SHIPPING WEIGHT- LB (KG)		HEATING ELEMENT	5350 W, 240V/ 4750W,208V
CYCLE TIME-MINUTES	45	TYPE OF GAS	FACTORY EQUIPED NATURAL
MOTER HP	1/3 HP,55 AMPS	(GAS MODELS ONLY)	MIXED GAS CONVERTABLE
CYCLE/TEMPERATURE	REGULAR PERM PRESS DELICATE NO HEAT	UTILITY CONNECTIONS	TO LP GAS **
		IN (MM)	GAS: 3/8*NPT (9.5)
AIR OUTLET DIAMETER-IN (MM)	4* (102)	AGENCY APPROVAL	ELECTRIC UL / GAS CSA STAR
EXHAUST AIRFLOW CFM (LITERS/SEC)	06*WC	ACTIVATION	PUSH-TO-START
		TOP AND LID FINISH	POWDER PAINT
		COLORS	WHITE