


SMART
LAUNDRY
TECHNOLOGY



XGQ Series Full Automatic
Washer Extractors





SMART
LAUNDRY
TECHNOLOGY



FEATURES

- ◆ PATENTED ANTI-VIBRATION STRUCTURE SPRING, SHOCK ABSORPTION REACHES TO %95 (PATENT NO. 200820056884.2). REAL MEANING OF FREE STANDING, NO DAMAGE TO MACHINE WHILE HIGH SPIN.
- ◆ JAPANESE MITSUBISHI V-BELTS, RUN SMOOTHLY.
- ◆ JAPANESE YASKAWA INVERTER.
- ◆ FREQUENCY CONTROLLED MOTOR.
- ◆ AMERICAN TWB BEARINGS
- ◆ FRENCH SCHNEIDER ELECTRIC PARTS. SAFETY AND RELIABLE.
- ◆ STAINLESS STEEL CABINET AND DRUM.
- ◆ IMPORTED VITON SEAL MAKES NO LEAKAGE.
- ◆ USB PORT MICROPROCESSOR ENABLES TO REPROGRAM FREELY & EASILY BY PC.
- ◆ EASY ACCESS TO ALL PARTS FOR MAINTENANCE.
- ◆ LARGE DRAIN VALVES AND TWO DRAIN CONNECTIONS AVAILABLE.
- ◆ EACH DRUM TESTED BY DYNAMIC BALANCE MACHINE AND THE GRAVITY DEVIATION NO MORE THAN 20G.
- ◆ 5 REMOVABLE COMPARTMENTS SOAP HOPPERS (ABOVE 30KG)
- ◆ ELECTRIC, STEAM HEATING.

DIMENSIONS & SPECIFICATIONS

MODEL		XGQ15-FII	XGQ20-FII	XGQ25-FII	XGQ30-FII	XGQ50-FII	XGQ70-FII	XGQ100-FII
CAPACITY								
Drum capacity	kg(lb)	15(33)	20(44)	25(55)	30(66)	50(110)	70(154)	100(220)
Drum diameter	mm	640	700	800	900	1065	1090	1210
Drum depth	mm	490	510	500	500	610	760	880
Drum volume	L	160	195	250	315	540	708	1010
DRUM SPEED								
Washing speed	rpm	50	48	45	37	36	35	34
Highest spin speed	rpm	800	780	750	750	720	700	680
HEATING								
Electric	kw	14	18	21	21	42	46	/
Steam ratio	kg/kg	0.9	0.9	0.9	0.9	0.9	0.9	0.9
CONNECTIONS								
Water inlet		ZG1.0"	ZG1.0"	ZG1.2"	ZG1.5"	ZG1.5"	ZG1.5"	ZG1.5"
Steam inlet		ZG3/4"	ZG3/4"	ZG3/4"	ZG1.0"	ZG1.0"	ZG1.0"	ZG1.0"
DIMENSIONS								
Size WxDxH	mm	930x1100 x1530	1000x1170 x1560	1150x1220 x1600	1460x1440 x1840	1610x1680 x2040	1650x1960 x2160	1760x2090 x1970
N.W.	kg	550	750	1200	1600	2250	2800	3200

MODEL		XGQ130-FII	XGQ100-T	XGQ130-T	XGQ100-G	XGQ130-G
CAPACITY						
Drum capacity	kg(lb)	130(286)	100(220)	130(286)	100(220)	130(286)
Drum diameter	mm	1320	1210	1320	1210	1320
Drum depth	mm	950	880	950	880	950
Drum volume	L	1300	1010	1300	1030	1300
DRUM SPEED						
Washing speed	rpm	32	34	32	34	32
Highest spin speed	rpm	635	680	635	720	690
HEATING						
Electric	kw	/	/	/	/	/
Steam ratio	kg/kg	0.9	0.9	0.9	0.9	0.9
CONNECTIONS						
Water inlet		ZG2.0"	ZG1.5"	ZG2.0"	ZG1.5"	ZG2.0"
Steam inlet		ZG1.5"	ZG1.0"	ZG1.5"	ZG1.0"	ZG1.5"
DIMENSIONS						
Size WxDxH	mm	1950x2220 x2175	1820x2390 x2200	2070x2580 x2340	1820x2410 x2170	2070x2580 x2300
N.W.	kg	4100	3200	4200	3300	4300