

SMART
LAUNDRY
TECHNOLOGY



Perchloroethylene based
Drycleaning Machine

MODEL


WDC10-10KG

WDC12-12KG



CLOSED CIRCUIT DRY CLEANING TECHNOLOGY TO ENSURE EFFICIENT CLEANING OF FABRICS THAT ARE NOT WATER SOLUBLE SUCH AS SILK & WOOL.

FULLY INTEGRATED WASHING, DRYING AND SOLVENT SELF CLEANING MECHANISM.



SMART LAUNDRY TECHNOLOGY



FEATURES

HIGH QUALITY RECYCLE COOLING SYSTEM, EFFICIENT RECOVERY OF SOLVENTS, REDUCING POLLUTION, SAVING SOLVENT.

MICROCOMPUTER-CONTROLLED, FULLY AUTOMATIC, LARGE LCD-DISPLAY, EASILY UNDERSTANDABLE.

THREE BOTTOM TANKS, SEPARATE CLEAN, DIRTY AND WORKING SOLVENT, AVOID MIXING SOLVENT, PROTECT THE MACHINE AND SAVE SOLVENT.

THE CENTRIFUGAL FILTER REMOVE IMPURITIES, PARTICLES, PIGMENT, ENSURE CLEAN SOLVENT, AVOID DYEING, BLOCKAGE.

DRUM IN STAINLESS STEEL, NON-FERROUS METALS STAMPING WITH MOLD CRAFTED, HIGH-TEMPERATURE GALVANIZING TECHNOLOGY, STRONG AND NICE.

HIGH-SPEED FAN, SPEED UP THE DRYING AND COOLING RATE.

SAFETY DOOR INTERLOCK SYSTEM, PROTECT OPERATOR.

EFFICIENT RECOVERY OF SOLVENTS, THUS REDUCING ENVIRONMENTAL IMPACT

FULLY AUTOMATIC MICROPROCESSOR CONTROLLED.

LARGE LCD DISPLAY AND USER FRIENDLY INTERFACE

CENTRIFUGAL FILTRATION ENSURES EFFICIENT REMOVAL OF PIGMENTS.

STAINLESS STEEL DRUM THAT ARE MOLD CRAFTED ENSURES LONGER LIFE.

SPECIFICATIONS

Model		WDC-10	WDC-12
Capacity	Kg	10	12
Drum Diameter	mm	718	718
Drum Depth	mm	430	480
Drum volume	l	174	196
Tank 1 Volume	l	95	100
Tank 2 Volume	l	85	90
Tank 3 Volume	l	98	100
Washing speed	r/min	38	38
High Spin Speed	r/min	400	400
Centrifugal Filter Volume	l	45	45
Pump Power	kw	0.37	0.55
Low Speed Power	kw	0.4	0.4
High Spin Speed Power	kw	1.5	1.5
Filter Motor Power	kw	0.55	0.55
Fan Motor Power	kw	0.55	0.55
Steam Heating Installation Power	kw	6.35	6.35
Electric Heating Installation Power	kw	16.5	16.5
Inlet of Water	mm	1/2	1/2
Outlet Pipe	mm	1/2	1/2
Cooling Water Pressure	mpa	0.2~0.4	0.2~0.4
Air Pressure	mpa	0.2~0.4	0.2~0.4
Dimension(L.W.H)	mm1	700×1360×2050	1520×1360×2110
Net Weight	Kg	900	950